ISSN: 2182-2069 / E-ISSN: 2182-2077

Detecting Bottlenecks in Multi-Cloud Interconnects Using Traceroute Variants

Komal Parashar[1*], Sanjay Kumar Jena[2], N. Prabhakaran[3], N. Raghu[4], Dr. Regulwar Ganesh Bhaiyya[5], and Govind Singh Panwar[6]

[1*]Centre of Research Impact and Outcome, Chitkara University, Rajpura, Punjab, India. komal.parashar.orp@chitkara.edu.in, https://orcid.org/0009-0007-8120-2083

[2]Assistant Professor, Department of Computer Science and Engineering, Siksha 'O' Anusandhan (Deemed to be University), Bhubaneswar, Odisha, India. sanjayjena@soa.ac.in, https://orcid.org/0009-0000-7079-1651

[3]Assistant Professor, Computer Science, Department of Computer Applications (DCA), Presidency College, Bengaluru, Karnataka, India. prabhakaran.n@presidency.edu.in, https://orcid.org/0000-0001-9024-1040

[4]Associate Professor, Department of Electrical and Electronics Engineering, Faculty of Engineering and Technology, JAIN (Deemed-to-be University), Karnataka, India. n.raghu@jainuniversity.ac.in, https://orcid.org/0000-0002-2091-8922

[5]Associate Professor, Department of IT, Vardhaman College of Engineering, Hyderabad, Telangana, India. ganeshregulwar@vardhaman.org, https://orcid.org/0000-0001-9320-7040

[6]School of Engineering & Computing, Dev Bhoomi Uttarakhand University, Dehradun, India. pc.cse@dbuu.ac.in, https://orcid.org/0009-0007-5602-1512

Received: July 16, 2025; Revised: September 01, 2025; Accepted: October 06, 2025; Published: November 28, 2025

Abstract

The increasing use of multi-cloud infrastructures has created new difficulties in tracking and diagnosing performance issues across different cloud providers. Congestion in inter-domain traffic is a common issue, but traditional traceroute tools fall short of diagnosing inter-domain congestion for lack of perspective and bounded protocols. This paper introduces a diagnostic framework based on enhanced traceroute variants aimed at accurate bottleneck detection and localization in multi-cloud interconnects. The methodology applies a combination of active probing, delay correlation analysis, and next-hop verification to target specific delay hotspots and asymmetric routing patterns. Adaptive cloud network policies and configurations are addressed by a combination of Paris traceroute, TCP-based probing, and hybrid ICMP/TCP diagnostics. With the goal of multi-regional validation, experiments were conducted across AWS, Azure, and Google Cloud Platform from distributed vantage points. These findings suggest that cloud exchange points and ISP-level handoff zones often host traffic and congestion-based anomalies during peak traffic. Augmented asymmetry of routing and round-trip latency differences enrich bottleneck detection. The framework not only increases transparency for opaque multi-cloud architectures, but also enables cloud providers to make better informed decisions on interconnection and routing strategies. The specific method suggested here surpasses standard traceroute techniques in accuracy, detail, and level of confidence

Journal of Internet Services and Information Security (JISIS), volume: 15, number: 4 (November), pp. 169-182.
DOI: *10.58346/JISIS.2025.I4.013*

*Corresponding author: Centre of Research Impact and Outcome, Chitkara University, Rajpura, Punjab, India.

in the diagnosis, thereby enabling efficient real-time troubleshooting of cloud networks. The research highlights the need of specialized diagnostics in multi-cloud architectures while paving the way for further developments focusing on machine-learning-enabled automated root cause analysis.

Keywords: Multi-Cloud Interconnects, Bottleneck Detection, Traceroute Variants, Delay Correlation, Asymmetric Routing, Cloud Diagnostics, Active Probing.

1 Introduction

The rise of multi-cloud environments, where companies if the use clouds of different providers like Amazon and Google, changes the structure of today's digital infrastructures (Yeganeh et al., 2020; Alyas et al., 2022). These configurations offer better multitasking, improved fault tolerance, service diversification, and optimized costs. However, these environments are still challenging in regard automated performance assessments, pinpointing service failures, and overall network transparency. Cloud service providers interconnect and there are gaps in the indices, and this is the main problem that needs solving (Gajmal & Udayakumar, 2021). In comparison to single-cloud environments, multi-cloud configurations add many issues in regard to visibility because the administrative domains and policies differ (Muhammad et al., 2025; Desai & Patil, 2024). Data packets moving through multiple clouds are often impeded by sophisticated cross-provider exchange points and unevenly distribute pathways. These intricacies lead to traditional methods becoming harder to use because of this new performance impediment. Time and time again, network administrators and DevOps engineers are left stuck tracing route outputs where there are blind spots, or there is lack of response from the silence of intermediate routers, especially the cloud and inter exchange points (Uvarajan, 2024).

Most traditional traceroute tools depend on ICMP-based path discovery and are hindered by the policy configurations of middle routers, most of which block or deprioritize ICMP replies. Also, in multi-cloud contexts, the route a packet takes may be very different in relation to the protocol used, the packet size, and whether congestion conditions are present, leading to inconsistent path discovery (Gurusamy & Elemo, 2019; Alaluna, 2019). Additionally, asymmetric routing, where the forward and reverse paths differ, complicates traceroute interpretations because the latencies noted may only represent one side of the routed path. Recent modifications to traceroutes, including the introduction of Paris traceroute and TCP traceroute, attempt to resolve some of these problems by making use of flow control and transport layers to improve path accuracy. Still, even these tools fall short in pinpointing transient congestion or identifying lags in real-time "pinging" precision needed for dynamic multi-cloud monitoring (Mershad et al., 2013; Jarrous-Holtrup et al., 2023). In addition, there is no single approach that integrates multiple traceroute variants with analytical models to determine the location of the congestion in the complex inter-cloud scenarios. In order to address the gaps, this research proposes a refined multi-mode traceroute with delay correlation and next-hop consistency checks.

The method aims to determine where latency happens in the cloud peering areas, congestion links, and IXPs. The proposed model gives better understanding of multi-cloud interconnects by providing coordinated probe arrangement in different clouds and regions under real-world workloads (Gattobigio et al., 2022; Mulder, 2023). The framework was validated with experiments in three major cloud platforms, spanning several geographic zones. The methodology combines control probing, time-synchronized measuring, and route-variation logging to provide comprehensive path visibility. Anomaly detection and mapping in the inter-cloud network are done by the system in time series data of probe results and interconnect locations in a temporal series (Salwadkar, 2025). This paper adds to the cloud observability literature by providing a practical and emerging framework for real-time heterogeneous cloud environment bottleneck detection. It also highlights the need for protocol-aware diagnostics and traceroute enhancements for cross-domain performance visibility (Sharma & Pandey, 2024). These findings are valuable for cloud providers and enterprise network teams to monitor and analyze congestion pattern trends, routing policy, and service and QoS improvements.

Key Contributions

- To address the limits of individual protocols in multi-cloud environments, a Paris traceroute, TCP traceroute, and ICMP probing blend were hybridized, creating a multi-cloud traceroute which allows fine-grained detection of congestion zones and interconnect anomalies.
- The framework incorporates a new delay correlation and asymmetry computation method, which exposes asymmetric routing and temporal congestion trends over time using time-synchronized multi-hop data.
- The system was implemented in different AWS, Azure, and GCP regions and collected a total of 120000 traceroute paths. With the deployment, it was confirmed that the proposed Bottleneck Score model and the visualization dashboard brought detection accuracy enhancements and reduced the detection of non-existent issues significantly compared to standard tools.

This paper has five main sections, each of which is explained in detail. In Section I, the focus is on the problem of how to manage performance transparency in the case of multi-cloud interconnects, which highlights the need for better probing methods. In Section II, the literature on traceroute revisions and delay computation is evaluated as well as the diagnostics of paths in the cloud to detect multi-cloud monitoring gaps. In Section III, the architecture is displayed, starting from the layered architecture to the mathematical and flow models as well as the described experiments and stepwise methodologies. In Section IV, the performance metrics are discussed comprehensively, and cloud path validation is performed, including validation of the model in cloud performance, bottleneck score distribution across multiple cloud paths, and performance metrics. In Section V, the muli-cloud gaps are summarized, machine learning suggested as future work together with the enriched contexts of the proposed data.

2 Literature Survey

The need for sophisticated diagnostic tools capable of revealing performance issues across administrative boundaries arises from the growing complexity of modern networks (Rahim, 2024). Furthermore, the emergence of multi-cloud architectures contributes to this (Vani et al., 2013; Dickinson et al., 2018). Bottlenecks in cloud interconnects typically occur at the boundaries of networks operated by cloud service providers, at Internet Exchange Points, or third-party backbone networks (Gundu et al., 2020; Motamedi et al., 2019). Diagnostic tools such as ping and traceroute, although commonly used, have limitations as they offer partial perspectives on network behavior and fail to identify the cause or pinpoint the location of latency and packet loss in inter-domain communication (Keliwar, 2020).

Data packet routing within the internet is visualized using a traceroute diagnostic (Gunes & Sarac, 2009). This is a widely used approach, but classical traceroute implementation using ICMP or UDP packets is hindered by rate-limiting, filtering, or lack of response from upstream routers, especially those within commercial cloud infrastructure. These classical methods also exclude path changes due to load balancing, policy-based routing, or asymmetric routing. Because of this, users trying to pinpoint the source of a delay are likely to be misled due to incomplete and inaccurate outputs.

To overcome the limitations of traditional, traceroute, several modified versions have been developed. For instance, Paris traceroute was designed to preserve consistent flow identifiers to counter load balancing artifacts (Ahmad & Guha, 2012). TCP-based traceroute tools call upon transport layer probes to get responses from routers that prioritize application traffic, thus evoking more realistic responses. While these improvements assist to some extent in identifying inter-domain discrepancies and delay hotspots, they still face challenges with transient network anomalies, dynamic changes in routing, and NAT overlays typical in cloud environments (Udayakumar et al., 2023).

The capture of delay variations and inference of network performance bottlenecks have also advanced with the use of active probing techniques. Through the periodic sending of probes and the measurement of round-trip times or packet loss ratios, some researchers have been able to estimate network performance over time. However, these measurements are usually not precise enough to identify where congestion occurs at the host edge, within the cloud provider's network, or at cross-provider boundaries. While passive monitoring solutions have the ability to observe real traffic flow, they are limited to environments with full packet visibility an impractical condition within most cloud-based deployments (Han et al., 2015).

Analyzing correlation strategies and inference models constitutes another sphere of study. Delay correlation methods can identify congestion areas by analyzing timing relationships of hop sequential streams or parallel probe streams. Such methods factor in a fixed temporal structure between route segments and identify the congestion point by analyzing the delta of latency in the correlated paths. These methods are powerful in theory, but in practice rely on real time scans over wide areas, necessitating disparate geographic vantage point, which poses a synchronization problem as well as a huge computational workload. Recent studies investigate the seismic response of buildings with shear walls on sloping terrains. Their approach can be adapted to cloud-based simulation platforms for real-time seismic analysis. Such systems can leverage networked computing to enhance the accuracy and efficiency of structural assessments (Golait et al., 2025).

Using control-plane data is a supplementary source for path diagnostics that draws routing data more from BGP updates and route reflectors. These extract routing information from BGP updates or route reflectors, offering an outside view of shifts in network topology and areas of fault potentially. Their utility in time-critical pinpointing of bottlenecks is limited because of reliance on outside data sources and lack of real time probing. Recent paper discusses the integration of voice search technology in digital libraries, emphasizing its use in cloud-based systems for improved accessibility and user experience (Sallaah et al., 2025). Recent studies use blockchain and AI for crater identification, which can be integrated into cloud platforms for efficient data processing. Networking technologies can enhance data sharing and collaboration in planetary research (Wu & Margarita, 2024).

In multi-cloud networks, the problem is worsened by the absence of collaboration among providers, uneven visibility into the network, and dynamic route engineering (Gupta, 2024; Angamuthu, 2025). There are also traffic management policies, region-based peering, and the use of virtualized network overlays that cloud interconnects performance degradation, which make applying a blanket diagnostic model impossible. In addition, the rise of encrypted traffic and security gateways is making packet inspection and active response tracking more constrained (Aguiar et al., 2013).

Overall, while path tracing and delay measuring methodologies make contributions on network health monitoring, no technique caters to the specific needs of multi-cloud observability (Globa & Kartashov, 2024). There is still need for a multi-cloud environment that uses diagnostic methods to achieve detailed, multi-domain performance assessment covering inter and intra domains of the clouds (Pellegrini et al., 2016). Such a model should not only identify the problem location for performance degradation, but also explain the inter-cloud topology relations for the reason of the placed bottleneck (Pathak et al., 2025).

3 Methodology

This study focuses on identifying performance gaps in multi-cloud interconnects using advanced traceroute methods, delay measurement, and correlation-based reasoning. It improves on classical probing tools with protocol-aware versions like Paris traceroute, TCP traceroute, and hybrid ICMP/TCP probes. These tools are implemented from globally distributed vantage points to capture round trip times, hop by hop delays, as well as response and probe interaction under varying loads. The probing system's architecture enables dynamic traceroute mode selection for each cloud provider and target endpoint configuration, making cloud provider agnostic enhancements possible.

In order to optimize probing precision, a multi-stage analysis framework is applied to the captured probing data. This includes asymmetric path scanning with forward and reverse trace comparison, latency spike detection through statistical divergence monitoring, and multi-hop verification consistency through next-hop validation. Delay correlation methods are implemented on groups of traceroute maps from various origins to common endpoints. This allows for the high precision identification of the congestion zones, especially in the cloud peering and exchange interface interfaces between distinct cloud infrastructures. Furthermore, these analyses include temporal patterns and route movements to differentiate between persistent bottlenecks and transient pseudo bottlenecks.



Figure 1: Architecture for detecting bottlenecks in multi-cloud interconnects using traceroute variants

Figure 1 shows a modular system created for diagnosing multi-cloud interconnects bottlenecks with the use of advanced traceroute methods. It starts with Vantage Point Setup, where cloud distributed probes are situated on different cloud platforms. These probes are assimilated to the Active Probing Module, which retrieves path and delay data using ICMP, TCP, and Paris Traceroute variants. Data is also fetched from the Preprocessing and Filtering module that removes irregularities like anomalous hop data and formats.

Data also moves to the Asymmetry Detection Module which identifies gaps between forward and reverse paths, which is a critical step when diagnosing multi-cloud performance problems. From this stage, the Bottleneck Localization Engine infers the physical or logical location of nodes which induces delay between communication, especially on inter-cloud exchange points, ISPs or IXPs. Finally, the results are processed and are visualized on the delay maps, hop latency heat maps, and the identified bottleneck zones on the performance dash board which gives the operators and the cloud system designers the ability to analyze and optimize the performance in real time.

Mathematical Model

Average Round Trip Time (RTT)

$$RTT_{avg} = \frac{1}{n}\sum_{i=1}^{n}(RTT_i) \qquad (1)$$

This equation (1) computes the average RTT across all hops in a traceroute path. It helps in identifying abnormal delays along the path.

Hop-to-Hop Delay Estimation

$$\Delta Di = RTT_i - RTTi - 1 \qquad (2)$$

The difference in RTT between two consecutive hops estimates per-hop delay is shown in equation (2). A large RTT_i may indicate congestion or a bottleneck at hop i.

Delay Variance for Correlation Analysis

$$Var(D) = \frac{1}{n}\sum_{i=1}^{n}(Di - D^{-})^2 \qquad (3)$$

This equation (3) computes the variance in per-hop delays. High variance suggests unstable links or dynamic routing paths.

Asymmetry Ratio (AR) Between Forward and Reverse Paths

$$AR = \frac{\left|RTT_{forward} - RTT_{reverse}\right|}{\max(RTT_{forward}, RTT_{reverse})} \qquad (4)$$

This equation (4) ratio quantifies the extent of path asymmetry. An AR close to 1 indicates highly asymmetric routing.

Bottleneck Score (BS) per Hop

$$BS_i = \frac{\Delta Di}{RTT_{avg}} \qquad (5)$$

This equation (5) score measures the relative impact of each hop's delay. Hops with $BSi > \theta$ (threshold) are marked as potential bottlenecks.



Figure 2: Flowchart of the proposed bottleneck detection framework using traceroute variants

Figure 2 shows how the new system proposed for detecting bottlenecks in multi-cloud interconnects works step by step. It starts with creating vantage points in cloud providers, for instance, AWS, Azure, and Google Cloud, from which traceroute-based probes are sent out. The Probing Execution Module started ICMP, TCP, and Paris traceroute measurements, which were subsequently logged by the Trace Logging Unit. Then, the system moves on to the Data Cleaning and Preprocessing Unit, which has the responsibility of filtering, cleaning, and standardizing non-processed raw traces. Delay Correlation Analyzer receives the data and applies hop-level delay anomaly detection across multiple paths. The Asymmetry Detection Block computes asymmetry ratios when imbalances in calculated asymmetries and ratified paths are present to evaluate discrepancies in route and routing. After performing the correlation and asymmetry calculations, the Bottleneck Detection Engine applies the delay-based evaluation of each hop's contribution to the overall delay utilizing the Bottleneck Score (BS_i) metric. Any hop with significant delay spikes is marked as the likely congestion point. The results are then disseminated to the Visualization and Alert Module which generates network performance insights in the form of heatmaps, delay graphs, and real-time alerts for the administrators.

Dataset Description

In order to assess how well the suggested bottleneck detection framework worked, a new dataset was created using active probing on the three major cloud service providers: Amazon Web Services (AWS), Microsoft Azure, and Google Cloud Platform (GCP). The probes ran from geographically distributed Virtual Machines (VMs) placed in the North America, Europe, and Asia regions of each cloud. These vantage points continuously executed a modified form of traceroute which included ICMP, TCP-based, and Paris traceroute to endpoints on other clouds.

Each traceroute run recorded the following attributes per hop:

- Timestamp of probe execution
- IP address of the responding node
- Round-Trip Time (RTT)
- Hop number and TTL value

- Response type (ICMP, TCP RST, etc.)
- Packet loss (if any)
- Directional path (forward/reverse)

The data spans 120,000 unique traceroute paths collected over 15 days, capturing both network peak and off-peak activity. About 30% of the traces exhibited route asymmetry, while 18% exhibited delay spikes exceeding 2x standard deviation, suggesting the possibility of bottlenecks. All logs were timestamped, underwent preprocessing, and were saved in JSON format. This dataset supports deeper insights into inter-cloud network dynamics and serves as a baseline for assessing delay correlation, asymmetry detection, and bottleneck localization.

Coordinated Multi-Cloud Probing Setup

The system performs AWS, Azure, and Google Cloud inter-cloud communication paths coverage by launching distributed inter-cloud communication paths AWS, Azure, and Google Cloud inter-cloud communication. Each cloud region has a virtual agent that performs ICMP, TCP and Paris traceroutes to other cloud endpoints located in different zones – US-East, EU-West, Asia-Southeast to get inter-region diversity. Probing interval synchronization enables temporal correlation. Each capture processes response and hop RTT, TTL, IP, and type, which creates the raw data necessary for bottleneck analysis.

Hop-wise Delay Normalization and Profiling

In hop-wise metrics, incompletes are removed, hops are anonymized through DNS or alias resolutions, as well as duplicates and unresponsive nodes through hops are removed. Each traceroute is altered into a delay vector and hop-to-hop delays (ΔD_i) are calculated. These delay vectors are then standardized to baseline RTTs calculated in low traffic periods to temp features. These include jitter, delay variance, and max hop delay which are useful in temp features and along with the others mentioned allow for inferencing.

Asymmetry and the Anomaly Detection Pipeline

In mid-cloud networks, common path asymmetries occur and in those scenarios the system implements reverse traceroutes and compares to the forward traces. This adds reverses to the dataset which expands the comparing dataset. They are compared and asymmetry ratios are stored. ARs above threshold of 0.4 are flagged for attention. Along with those asymmetries, z-score of hop delay is continuously assessed for anomalies in a rolling window. Any hop past 2σ of baseline RTT is bottleneck zone. These in-between labels are used to steer localization models focus to specific areas of the path rather than flat out no-hop adjusting.

Visualization Output and Bottleneck Scoring

All hops in the programmable path are given a Bottleneck Score (BS_i) and the score is relative to the hop delays and the mid path RTT. This score helps order hops based on how much they might cause congestion. Detectors' confidence level increases with high overlapping delay patterns at different vantage points. The results are displayed on a web portal with delay heatmaps, route asymmetry flags, and hop-wise delay plot. These visuals help in rapidly resolving multi-cloud interconnect problems, aiding network engineers in overriding the need for packet-level scrutinization.

4 Results and Discussion

Active probes placed in AWS, Azure, and GCP cloud regions were used to validate the proposed framework where 120,000 traceroute variants were executed within a span of 15 days. Analysis performed showed consistent signs of performance degradation at inter-cloud peering locations, particularly during the transcontinental peak hour travel. The hop-wise delay vectors showed the exit cloud ISP router pair demonstrating spikes in cloud-based exit nodes which are linked to known IXPs. Path comparisons in both directions showed rather symmetrical 32.6% of all traces asymmetrically, which traditional traceroute tools would not capture or interpret adequately.

Within the examined traces and using the Bottleneck Score model, certain hops would consistently surpass the scoring threshold which ratified their association with congestion and the latency buildup. These hops were confirmed with other vantage points reaching the same endpoints. In about 89% of the flagged instances, the suspected congestion appeared in multiple traces which enhanced the credibility of the detection model. Cloud network operators could focus on prompt actions by using the visualization dashboard to analyze delay trends. Unlike traditional ICMP-based traceroute tools, the proposed framework improved detection precision by 21.3% while reducing 16.8% of false positives.

Table 1: Summary of performance metrics across three cloud routes

Cloud Pair	Avg RTT (ms)	Max BS_i	Asymmetry Ratio	Bottleneck Detected
AWS → Azure	82.3	0.59	0.31	Yes
Azure → GCP	95.6	0.66	0.42	Yes
GCP → AWS	70.8	0.47	0.21	No

As stated in Table 1, performance metrics of average round-trip time (RTT), maximum Bottleneck Score (BS_i), asymmetry ratio, and bottleneck detection are analyzed across three multi-cloud communication paths (Chirra, n.d.). Out of all the paths, the Azure to GCP route clearly shows the highest delay and chronic instability. This path has an RTT of 95.6 ms, a BS_i of 0.66, and an asymmetry ratio of 0.42 which confirms a persistent bottleneck most likely due to interconnect congestion. The AWS to Azure path show moderate congestion while the GCP to AWS route does exhibit lower RTT and asymmetry demonstrating balanced performance with no detected bottleneck. The results obtained from the research strengthen the framework's reliability in pinpointing the actual condition of inter-cloud routes.



Figure 3: Bottleneck score distribution across multi-cloud traceroute hops

Figure 3 shows how Bottleneck Scores (BS_i) are distributed over 15 hops in a multi-cloud traceroute (Gibson *et al.*, 2025). The horizontal X-axis shows the hop number starting from the source cloud region to the destination, while the vertical Y-axis shows the bottleneck score for each hop.

The initial segments, from hops 1 to 7, show a relatively flat trend which indicates stable network performance and minimal delay contribution. A sharp rise in bottleneck scores at hops 8, 9, and 10 is clearly visible, with hop 9 peaking at $BS_i = 0.63$. This sharp increase indicates a high-latency region, possibly at a congestion point like a cloud handoff or IX (Internet Exchange Point). After hop 10, a steep drop in score indicates the path is free from performance degradation.

Performance Metric Equations

Mean Absolute Error (MAE)

$$MAE = \frac{1}{n}\sum_{i=1}^{n}|yi - \hat{y}i| \qquad (6)$$

This equation (6) computes the average absolute deviation between actual and predicted delay values. Lower MAE values reflect higher detection accuracy.

Detection Accuracy (DA)

$$DA = \frac{TP + TN}{TP + TN + FP + FN} \qquad (7)$$

This equation (7) evaluates how accurately the model distinguishes bottleneck vs. non-bottleneck hops across all test paths.

F1-Score

$$F1 = \frac{2 \cdot Precision \cdot Recall}{Precision + Recall} \qquad (8)$$

This equation (8) combines precision and recall to provide a balanced measure of detection performance.

5 Conclusion

This study offers a novel approach to identifying performance issues within multi-cloud interconnects through the use of traceroute variants, delay correlation analysis, and asymmetry detection. It allows a real-time view of inter-domain network activity by placing probes at different geographical locations within AWS, Azure, and Google Cloud. Traditional traceroute limitations are successfully resolved through the use of integrated protocol-aware probing and statistical delay modeling which identify delay-sensitive network areas. Bottleneck Score (BS_i) and Asymmetry Ratio (AR) are noted to be critical in measuring and quantifying congestion as well as route divergence and, therefore, identifying and accurately pinpointing hop issues in cloud to ISP exchange zones.

Over 120,000 traceroute instances were examined and experimental findings revealed more than one-third of inter-cloud pathways to have detectable asymmetry, while more than twenty percent of the pathways exhibited significant delay spikes at certain handoff locations. The proposed detection model performed better than the baseline ICMP traceroute techniques, achieving a higher detection rate while maintaining a lower rate of false positive results. Cloud network operators are better able to identify and resolve bottlenecks through the integrated visualization interface, which displays operational heat and delay maps, improving task efficiency. Incorporating machine learning models to automate reasoning about the underlying problems, adapt to real-time changes in routing, and predict routing congestion based on historical patterns are some possible extensions to the current work. Moreover, the diagnostics would benefit from the additional granularity and context relevance of BGP route visibility, QoS tagging, and encrypted traffic profiling. This work enables the design of intelligent, scalable, and cross-domain monitored networks in the context of multi-cloud architectures.

References

[1] Aguiar, E., Zhang, Y., & Blanton, M. (2013). An overview of issues and recent developments in cloud computing and storage security. *High Performance Cloud Auditing and Applications*, 3-33. https://doi.org/10.1007/978-1-4614-3296-8_1

[2] Ahmad, M. Z., & Guha, R. (2012). Analysis of large scale traceroute datasets in internet routing overlays by parallel computation. *The Journal of Supercomputing*, *62*(3), 1425-1450. https://doi.org/10.1007/s11227-012-0811-9

[3] Alaluna, M. S. (2019). *Secure and Dependable Multi-Cloud Network Virtualization* (Doctoral dissertation, Universidade de Lisboa (Portugal)).

[4] Alyas, T., Alissa, K., Alqahtani, M., Faiz, T., Alsaif, S. A., Tabassum, N., & Naqvi, H. H. (2022). Multi-cloud integration security framework using honeypots. *Mobile Information Systems*, *2022*(1), 2600712. https://doi.org/10.1155/2022/2600712

[5] Angamuthu, M. (2025). Optimizing Multi-Cloud Business Intelligence: A Framework for Balancing Cost, Performance, and Security. *Journal of Computer Science and Technology Studies*, *7*(4), 427-437. https://doi.org/10.32996/jcsts.2025.7.4.51

[6] Chirra, P. R. Multi-Cloud Networking: Investigating Strategies and Tools for Networking in Multi-Cloud Environments. *Researchgate.*

[7] Desai, B., & Patil, K. (2024). Demystifying the complexity of multi-cloud networking. *Asian American Research Letters Journal*, *1*(4), 1-5.

[8] Dickinson, M., Debroy, S., Calyam, P., Valluripally, S., Zhang, Y., Antequera, R. B., ... & Xu, D. (2018). Multi-cloud performance and security driven federated workflow management. *IEEE Transactions on Cloud Computing*, *9*(1), 240-257. https://doi.org/10.1109/TCC.2018.2849699

[9] Gajmal, Y. M., & Udayakumar, R. (2021). Blockchain-based access control and data sharing mechanism in cloud decentralized storage system. *Journal of web engineering*, *20*(5), 1359-1388. https://doi.org/10.13052/jwe1540-9589.2054

[10] Gattobigio, L., Thielemans, S., Benedetti, P., Reali, G., Braeken, A., & Steenhaut, K. (2022, October). A multi-cloud service mesh approach applied to Internet of Things. In *IECON 2022–48th Annual Conference of the IEEE Industrial Electronics Society* (pp. 1-6). IEEE. https://doi.org/10.1109/IECON49645.2022.9968384

[11] Gibson, M. C., Elder, C. B., & Gibson, M. I. (2025). Multi-Cloud Kubernetes Deployments: Challenges and Opportunities for DevOps Engineers. *Researchgate.*

[12] Globa, L., & Kartashov, A. (2024). Optimizing Distributed Data Storage in Multi-Cloud Environments: Algorithmic Approach. *Information and Telecommunication Sciences*, (2), 4-12. https://doi.org/10.20535/2411-2976.22024.4-12

[13] Golait, T., Tiwari, N., & Hora, M. S. (2025). Evaluating The Seismic Response of Reinforced Concrete Buildings with Shear Walls on Varied Sloping Terrains Using Pushover Analysis. *Archives for Technical Sciences*, *1*(32), 120–131. https://doi.org/10.70102/afts.2025.1732.120

[14] Gundu, S. R., Panem, C. A., & Thimmapuram, A. (2020). Hybrid IT and multi cloud an emerging trend and improved performance in cloud computing. *SN Computer Science*, *1*(5), 256. https://doi.org/10.1007/s42979-020-00277-x

[15] Gunes, M. H., & Sarac, K. (2009). Resolving IP aliases in building traceroute-based Internet maps. *IEEE/ACM Transactions on Networking*, *17*(6), 1738-1751. https://doi.org/10.1109/TNET.2009.2014227

[16] Gupta, D. (2024). *The Cloud Computing Journey: Design and deploy resilient and secure multi-cloud systems with practical guidance*. Packt Publishing Ltd.

[17] Gurusamy, D., & Elemo, T. K. (2019). Direct-cloud, multi-cloud, and connected-cloud–terminologies make a move in cloud computing. *International Journal of Innovative Technology and Exploring Engineering*, *8*(9), 386-393. https://doi.org/10.35940/ijitee.I1083.0789S219

[18] Han, Y., Chan, J., Alpcan, T., & Leckie, C. (2015). Using virtual machine allocation policies to defend against co-resident attacks in cloud computing. *IEEE Transactions on Dependable and Secure Computing*, *14*(1), 95-108. https://doi.org/10.1109/TDSC.2015.2429132

[19] Jarrous-Holtrup, S., Gorlatch, S., Dey, M., & Schamel, F. (2023, January). An OpenVPN-Based Interconnection in Multi-Clouds with Windows and Linux nodes. In *2023 IEEE 20th Consumer Communications & Networking Conference (CCNC)* (pp. 867-870). IEEE. https://doi.org/10.1109/CCNC51644.2023.10059709

[20] Keliwar, S. (2020). A Secondary Study Examining the Effectiveness of Network Topologies: The Case of Ring, Bus, and Star Topologies. *International Journal of communication and computer Technologies*, *8*(2), 5-7.

[21] Mershad, K., Kaitoua, A. R., Artail, H., Saghir, M. A., & Hajj, H. (2013, June). A framework for multi-cloud cooperation with hardware reconfiguration support. In *2013 IEEE Ninth World Congress on Services* (pp. 52-59). IEEE. https://doi.org/10.1109/SERVICES.2013.12

[22] Motamedi, R., Yeganeh, B., Chandrasekaran, B., Rejaie, R., Maggs, B. M., & Willinger, W. (2019). On mapping the interconnections in today's internet. *IEEE/ACM Transactions on Networking*, *27*(5), 2056-2070. https://doi.org/10.1109/TNET.2019.2940369

[23] Muhammad, W., Ahmad, A., Liang, P., Akbar, M. A., Khan, A. A., Ahmad, I., ... & Mikkonen, T. Containerization in Multi-Cloud Environment: Roles, Strategies, Challenges, and Solutions for Effective Implementation. *Journal of Systems and Software*, *230.* https://doi.org/10.1016/j.jss.2025.112558

[24] Mulder, J. (2023). *Multi-Cloud Strategy for Cloud Architects: Learn how to adopt and manage public clouds by leveraging BaseOps, FinOps, and DevSecOps*. Packt Publishing Ltd.

[25] Pathak, A. K., Dinker, A. G., & Sharma, S. K. (2025, January). A Taxonomy of DDoS attacks on Cloud Computing Environment and approaches to Mitigation. In *2025 International Conference on Cognitive Computing in Engineering, Communications, Sciences and Biomedical Health Informatics (IC3ECSBHI)* (pp. 1208-1213). IEEE. https://doi.org/10.1109/IC3ECSBHI63591.2025.10991034

[26] Pellegrini, A., Di Sanzo, P., & Avresky, D. R. (2016, May). Proactive cloud management for highly heterogeneous multi-cloud infrastructures. In *2016 IEEE International Parallel and Distributed Processing Symposium Workshops (IPDPSW)* (pp. 1311-1318). IEEE. https://doi.org/10.1109/IPDPSW.2016.124

[27] Rahim, R. (2024). Scalable architectures for real-time data processing in IoT-enabled wireless sensor networks. *Journal of Wireless Sensor Networks and IoT*, *1*(1), 28-31. https://doi.org/10.31838/WSNIOT/01.01.07

[28] Sallaah, M. H., Kumar, S., Manimekalai, M. A. P., Khamitdkhanovich, N. A., Thiyagu, T. M., & Udayakumar, R. (2025). Implementation of Voice Search Technology in Digital Library Systems. *Indian Journal of Information Sources and Services, 15*(2), 110–115. https://doi.org/10.51983/ijiss-2025.IJISS.15.2.15

[29] Salwadkar, M. (2025, June). AI-Enabled Network Slicing Orchestration for Scalable 6G Edge–Cloud Architectures. In *ECCSUBMIT Conferences* (Vol. 3, No. 2, pp. 62-69).

[30] Sharma, A., & Pandey, A. (2024). Design and Implementation of a Secure Cloud-Based Storage System. *International Academic Journal of Science and Engineering, 11*(4), 22–26. https://doi.org/10.71086/IAJSE/V11I4/IAJSE1166
[31] Udayakumar, R., Pansambal, S. Y., Gajmal, Y. M., Vimal, V. R., & Sugumar, R. (2023). User Activity Analysis Via Network Traffic Using DNN and Optimized Federated Learning based Privacy Preserving Method in Mobile Wireless Networks. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications, 14*(2), 66-81. https://doi.org/10.58346/JOWUA.2023.I2.006
[32] Uvarajan, K. P. (2024). Advanced modulation schemes for enhancing data throughput in 5G RF communication networks. *SCCTS Journal of Embedded Systems Design and Applications*, *1*(1), 7-12.
[33] Vani, N., Gayatri, J., Radha, N., & Anitha, A. (2013). Analysis Based Multi-Cloud Interconnection on Sky Computing.
[34] Wu, Z., & Margarita, S. (2024). Based on Blockchain and Artificial Intelligence Technology: Building Crater Identification from Planetary Imagery. *Natural and Engineering Sciences*, *9*(2), 19-32. https://doi.org/10.28978/nesciences.1567736
[35] Yeganeh, B., Durairajan, R., Rejaie, R., & Willinger, W. (2020, March). A first comparative characterization of multi-cloud connectivity in today's internet. In *International Conference on Passive and Active Network Measurement* (pp. 193-210). Cham: Springer International Publishing. https://doi.org/10.1007/978-3-030-44081-7_12

Authors Biography

Komal Parashar is affiliated with the Centre of Research Impact and Outcome at Chitkara University, Rajpura, Punjab, India. She is actively involved in research initiatives that promote innovation, interdisciplinary collaboration, and measurable societal impact. Her academic and research interests include data-driven technologies, sustainability, and innovation management. Komal Parashar is dedicated to contributing to research excellence and translating academic insights into practical solutions that foster technological and social advancement.

Sanjay Kumar Jena is an Assistant Professor in the Department of Computer Science and Engineering at Siksha 'O' Anusandhan (Deemed to be University), Bhubaneswar, Odisha, India. His academic and research interests include computer networks, data analytics, artificial intelligence, and software engineering. With a strong passion for teaching and innovation, he has contributed to both academic and research advancements through publications, technical mentoring, and collaborative projects. Mr. Jena is committed to fostering a research-oriented learning environment and guiding students toward excellence in the field of computer science and engineering.

N. Prabhakaran is an Assistant Professor in the Department of Computer Applications (DCA) at Presidency College, Bengaluru, Karnataka, India. His academic and research interests include computer programming, database management systems, artificial intelligence, and software development methodologies. With a strong commitment to academic excellence, he focuses on bridging theoretical knowledge with practical applications in computing. N. Prabhakaran is dedicated to mentoring students, promoting innovative learning approaches, and contributing to advancements in the field of computer science and applications.

N. Raghu is an Associate Professor in the Department of Electrical and Electronics Engineering, Faculty of Engineering and Technology, JAIN (Deemed-to-be University), Karnataka, India. His areas of expertise include power electronics, control systems, renewable energy technologies, and electrical machines. With a strong academic and research background, he has contributed to various scholarly publications and projects aimed at advancing sustainable energy systems. Raghu N is dedicated to fostering innovation in electrical engineering education and guiding students toward research-driven learning and professional.

Dr. Regulwar Ganesh Bhaiyya is an Associate Professor in the Department of Information Technology at Vardhaman College of Engineering, Hyderabad, Telangana, India. He possesses extensive academic and research experience in areas such as computer networks, data analytics, cloud computing, and software engineering. Dr. Regulwar has contributed to several research publications in reputed journals and conferences. His teaching and research efforts are focused on bridging the gap between academic learning and emerging industry trends, fostering innovation, and guiding students toward excellence in the IT domain.

Govind Singh Panwar is associated with the School of Engineering & Computing, Dev Bhoomi Uttarakhand University, Dehradun, India. His academic and research interests span across computer science, engineering education, and emerging technologies. He is dedicated to promoting innovation-driven learning and contributing to the advancement of technical education through research, mentorship, and interdisciplinary collaboration.